


**Durable,
Long-lasting
Punches &
Punch Blanks**

TUFFPUNCH[®]



Global leader in
providing fabrication
and stamping solutions

a MISUMI Group Company

www.daytonlamina.com

**Now including TRUMPET HEAD tooling
conforming to DIN/ISO standards**

**Heads-
above-the-rest
performance**



TuffPunch® Punches and Punch Blanks

Product Applications

Dayton Lamina TuffPunch® Punches and Punch Blanks are Kommercial quality products manufactured with thicker, larger, and 10° angled diameter heads, and are designed to reduce punch load and significantly lower failure rates when using heavy gauge and high tensile material. (See p. 3 for additional information.) TuffPunch® products are well-suited for high-demand industries where frequency and heavier-than-normal impact punching activity occurs and where optimum performance is required.

Dayton's TuffPunch® product line includes: Dayton Jektrole® Punches; Regular Punches; Center Dowel Punches; Punch Blanks; and Retainers. Both standard sizes and standard alterations are shown in this catalog.

Minimizes Head Failure

All Dayton TuffPunch® products are designed with a 10°-angled head with a diameter equal to the shank diameter (see photo). This design allows the perforating forces to travel up from the shank and completely through the head. This eliminates the lateral shock waves that would otherwise put stress on the outer edge of the head, resulting in frequent failures—especially in heavy-duty applications.

In addition, Dayton TuffPunch® products are available in common shear angle configurations to reduce punch load and minimize the risk of slug pulling. Shear angle configurations include: chamfer; conical; double shear; and single shear. For more information, see "Standard Alterations" on p. 9.

Cryogenic Treatment Standard

DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products.

The DayKool™ process utilizes a liquid nitrogen vapor to cool the steel to -184° C (-300° F), which creates metallurgical changes in the structure that disperse carbides throughout the metal. The result: increased wear resistance (finely dispersed carbides provide more evenly distributed wear); less sharpening time; no loss of resistance after sharpening; longer die runs; and less downtime.



Surface Coatings

Punches can be coated to increase material hardness, reduce galling, and improve wear/and or corrosion resistance.

Surface Treatments

DayTride® (XN)—A low temperature, cost-effective surface application that treats all exposed surfaces. Provides increased dimensional stability. Ideal for punches and die buttons. Approx. hardness: RC65-73.

XVP—A thin film coating provides superior hardness (harder than carbide). Super-smooth finish on the point helps reduce galling and maintenance. Ideal for higher-than-normal punching frequency.

XPS—Super-smooth polish on the point to reduce galling and improve punch life. Use with the appropriate coating for your application to maximize punch life and reduce maintenance costs. Excellent for extruding applications.

Abrasive Wear

DayTiN® (XNT)—Excellent wear resistance and lubricity. Not recommended for stainless steel, copper, or nickel. A good general-purpose coating. Approx. hardness: *Vickers 2300.

TiCN (XCN)—Ultra-hard (harder than carbide), thin coating. Provides superior abrasive wear resistance and lubricity. A very good general-purpose coating for all materials. Upgrade over XNT. Approx. hardness: *Vickers 3000.

DayTAN™ (XAN)—Ultra-hard (harder than carbide), high-aluminum coating. Provides high temperature resistance. Well-suited for applications where surface heat is generated. Ideal for HSLA, dual phase, and TRIP steels. Upgrade over XCN. Approx. hardness: *Vickers 3400.

ZertonPlus™ (XNA)—Superior hardness (harder than carbide); provides superior abrasive wear resistance and excellent lubricity. Provides highest temperature resistance, thermal shock stability, & hot hardness. Approx. hardness: *Vickers 3200.

Adhesive Wear

XNM—A solid lubricant coating. Provides both lubricity and wear resistance not available from other PVD or CVD processes. Ideal for aluminum, copper, pre-painted, and galvanized steels. Approx. hardness: *Vickers 2000.

XCD—Diamond-like carbon coating. Combines high hardness with an extremely low coefficient of friction. Good protection against abrasive and adhesive wear. Ideal for aluminum. Approx. hardness: *Vickers 5000.

XCDH—Super-smooth finish combined with advanced DLC coating for a very low coefficient of friction with extremely high wear resistance. Approx. hardness: *Vickers 5000.

XCDP—Super-smooth finish combined with a DLC coating for a very low coefficient of friction with high wear resistance. Excellent for stamping aluminum. Approx. Hardness: Vickers 2800.

Extrusion Coatings

XNP—The ultimate coating for improved resistance to galling; excellent wear resistance, superior surface finish, and high lubricity. Ideal for extruding and forming applications. Tolerance is ±.005 mm. Approx. hardness: *Vickers 3100.

XNAPprogress (XNAP)—Ultra-hard coating that absorbs shear stress; provides excellent high-temperature resistance. Ideal for stamping where tools are exposed to extreme stress profiles. A good alternative to TD coating without the dimensional changes associated with that process. Approx hardness: *Vickers 3200.

Miscellaneous Coating


CRN—Excellent adhesion, high toughness, and good corrosion resistance. Primary applications are metal forming (copper, brass, & bronze), metal die casting, and plastic injection molding. Approx. hardness: *Vickers 1800-2100.

*Vickers used when RC exceeds 80.

TuffPunch®, DayKool™, DayTAN™, ZertonPlus™, Daytride® and DAYTiN® are trademarks of Dayton Lamina Corp.

A black, triangular mechanical part with a large circular hole on the right side and several smaller holes on the top surface.

HOW TO ORDER




Jektrole®
with
Keeper Key

There are several features that contribute to minimizing failures. In addition to the head design and large fillet under the head, all punch shapes with sharp corners will have a carefully blended radius ground to reduce loading on the punch. The reduced load and standard cryogenic treatment result in fewer punch point problems caused by chipping, wear, or breakage.

The diagram shows a drill bit with the following labels and dimensions:


- APXF**: Line Product Shape Code. Legend: A for Press-Fit, P for Punch (Regular), X for Round, F for TuffPunch®.
- 16**: Press-Fit Dia. D (shank diameter)
- 19**: Point Length (L_1)
- 80**: Overall Length
- Product**: APXF
- Series**: 16
- Length**: 80
- Point or Hole Size**: P8.3
- Type**: APXF
- Catalog Number**: 16 19 80
- Dimensions, as specified**: P8.3

TuffPunch® Jektol® Punches




Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOWTOORDER

Specify:	Qty.	Type	D Code	L	P (or P&W) Dimension
Example:	6	AJXF	16	19-80	P 10.3
	12	AJRF	16	25-80	P 10.5, W 8.0
	10	AJLF	16	19-90	P 10.2, W 7.2



- 1 Check your P&W dimensions to be certain the diagonal G does not exceed the maximum shown.
- 2 Centerline to flat minimum = 2.0 for J6 and 3.0 for J9.

Note: Sharp corners will have a 0.13 radius to minimize wear.

Note: The standard location of a key flat is parallel to the P dimension. For additional information, see p.13.

Standard Alterations
See p.12 for additional ordering instructions.


Shank D	Point Length L ₁		Type & D AJXF	Range P	Type & D AJ_F	Min. W	Max. P/G	L						Jektol® Group
	Std.	Alt.						50	60	70	80	90	100	
08	13	19	AJXF 08	4.00 – 7.99	AJ_F 08	4.00 – 8.00							J4M	
10	13	19	AJXF 10	5.00 – 9.99	AJ_F 10	5.00–10.00							J6M	
13	13	19	AJXF 13	6.00–12.99	AJ_F 13	6.00–13.00							J6M	
16	19	25	AJXF 16	10.00–15.99	AJ_F 16	6.00–16.00							J9M	
20	19	25	AJXF 20	13.00–19.99	AJ_F 20	6.00–20.00							J9M	
25	19	25	AJXF 25	18.00–24.99	AJ_F 25	6.00–25.00							J9M	

Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.

● When L = 50, L₁ is 8.0.


● Alternate point length not available.

TuffPunch® Jektol® Punch Blanks



Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



Jektol® side hole position allows alternate point lengths shown on AJ_F above.

HOWTOORDER


Specify:	Qty.	Type	D Code	L
Example:	6	AJBF	20	80

Standard Alterations
See p.12 for additional ordering instructions.

Shank D	Catalog Number	L						Jektol® Group
		50	60	70	80	90	100	
08	AJBF 08	●	●	●	●	●	●	J4M
10	AJBF 10	●	●	●	●	●	●	J6M
13	AJBF 13	●	●	●	●	●	●	J6M
16	AJBF 16	●	●	●	●	●	●	J9M
20	AJBF 20		●	●	●	●	●	J9M
25	AJBF 25		●	●	●	●	●	J9M

Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.


TuffPunch® Regular Punches



Type
AP_F


Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOWTOORDER

Specify:	Qty.	Type	D Code	L	P (or P&W) Dimension
Example:	6	APXF	16	19-80	P 10.3
	12	APRF	16	25-80	P 10.5, W 8.0
	10	APLF	16	19-70	P 10.2, W 7.2



Note: The standard location of a key flat is parallel to the P dimension. For additional information, see p.13.

Standard Alterations
See p.12 for additional ordering instructions.

Shank D	Point Length L ₁		Type & D APXF	Range P	Type & D AP_F	Min. W	Max. P/G	L					
	Std.	Alt.						50	60	70	80	90	100
08	13	19	APXF 08	3.00 – 7.99	AP_F 08	3.00 – 8.00		●	●	●	●	●	●
10	13	19	APXF 10	3.00 – 9.99	AP_F 10	3.00–10.00		●	●	●	●	●	●
13	13	19	APXF 13	6.00–12.99	AP_F 13	3.00–13.00		●	●	●	●	●	●
16	19	25	APXF 16	10.00–15.99	AP_F 16	4.00–16.00		●	●	●	●	●	●
20	19	25	APXF 20	13.00–19.99	AP_F 20	5.00–20.00		●	●	●	●	●	●
25	19	25	APXF 25	18.00–24.99	AP_F 25	6.00–25.00		●	●	●	●	●	●

Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.

- When L = 50, L₁ is 8.0.
- Alternate point length not available.


TuffPunch® Regular Punch Blanks



Type
APBF

Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOWTOORDER


Specify:	Qty.	Type	D Code	L
Example:	6	APBF	20	80

Standard Alterations
See p.12 for additional ordering instructions.

Shank D	Catalog Number	L					
		50	60	70	80	90	100
08	APBF 08	●	●	●	●	●	●
10	APBF 10	●	●	●	●	●	●
13	APBF 13	●	●	●	●	●	●
16	APBF 16	●	●	●	●	●	●
20	APBF 20		●	●	●	●	●
25	APBF 25		●	●	●	●	●


Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.

TuffPunch® Jektol® Center Dowel Punches




Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOWTOORDER


Specify:	Qty.	Type	D Code	L	P (or P&W) Dimension
Example:	10	SJXF	20	80	P 13.3
	10	SJRF	25	80	P 14.5, W 8.0
	16	SJLF	20	90	P 13.2, W 7.2



- 1 Check your P&W dimensions to be certain the diagonal G does not exceed the maximum shown.
- 2 Centerline to flat minimum = 2.0 for J6 and 3.0 for J9.

Note: Sharp corners will have a 0.13 radius to minimize wear.

Note: The standard location of a key flat is parallel to the P dimension. For additional information, see p.13.



Standard Alterations
See p.12 for additional ordering instructions.

Shank D	Point Length L ₁	Type & D SJXF	Range P	Type & D SJ_F	Min. W	Max. P/G	L						Jektol® Group
	Std.	Alt.					80	90	100	110	120	130	
10	13	19	SJXF 10	5.0 – 9.99	SJ_F 10	5.00–10.00	●	●	●	●	●	●	J6M
13	13	19	SJXF 13	6.0–12.99	SJ_F 13	6.00–13.00	●	●	●	●	●	●	J6M
16	19	25	SJXF 16	10.0–15.99	SJ_F 16	6.00–16.00	●	●	●	●	●	●	J9M
20	19	25	SJXF 20	13.0–19.99	SJ_F 20	6.00–20.00	●	●	●	●	●	●	J9M
25	19	25	SJXF 25	18.0–24.99	SJ_F 25	6.00–25.00	●	●	●	●	●	●	J9M
32	19	25	SJXF 32	20.0–31.99	SJ_F 32	6.00–32.00	●	●	●	●	●	●	J9M
38	19	25	SJXF 38	28.0–37.99	SJ_F 38	6.00–38.00	●	●	●	●	●	●	J9M
45	19	25	SJXF 45	35.0–44.99	SJ_F 45	6.00–45.00	●	●	●	●	●	●	J9M


Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.

TuffPunch® Jektol® Center Dowel Blanks



Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



Jektol® side hole position allows alternate point length shown on SJ_F above.

HOWTOORDER


Specify:	Qty.	Type	D Code	L
Example:	9	SJBF	38	120

Standard Alterations
See p.12 for additional ordering instructions.


Shank D	Catalog Number	L						Jektol® Group
		80	90	100	110	120	130	
10	SJBF 10	●	●	●	●	●	●	J6M
13	SJBF 13	●	●	●	●	●	●	J6M
16	SJBF 16	●	●	●	●	●	●	J9M
20	SJBF 20	●	●	●	●	●	●	J9M
25	SJBF 25	●	●	●	●	●	●	J9M
32	SJBF 32	●	●	●	●	●	●	J9M
38	SJBF 38	●	●	●	●	●	●	J9M
45	SJBF 45	●	●	●	●	●	●	J9M

Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.

TuffPunch® Regular Center Dowel Punches




Material
Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOWTOORDER

Specify:	Qty.	Type	D Code	L	P (or P&W) Dimension
Example:	10	SPXF	20	90	P 13.3
	16	SPRF	25	80	P 19.5, W 9.0
	16	SPLF	20	90	P 13.2, W 7.2




Note: The standard location of a key flat is parallel to the P dimension. For additional information, see p.13.

Standard Alterations
See p.12 for additional
ordering instructions.


Shank D	Point Std.	Length L ₁ Alt.	Type & D SPXF	Range P	Type & D SP_F	Min. W	Max. P/G	L					
								80	90	100	110	120	130
10	13	19	SPXF 10	3.00 – 9.99	SP_F 10	3.00–10.00	●	●	●	●	●	●	
13	13	19	SPXF 13	6.00–12.99	SP_F 13	3.00–13.00	●	●	●	●	●	●	
16	19	25	SPXF 16	10.00–15.99	SP_F 16	4.00–16.00	●	●	●	●	●	●	
20	19	25	SPXF 20	13.00–19.99	SP_F 20	5.00–20.00	●	●	●	●	●	●	
25	19	25	SPXF 25	18.00–24.99	SP_F 25	6.00–25.00	●	●	●	●	●	●	
32	19	25	SPXF 32	20.00–31.99	SP_F 32	6.00–25.00	●	●	●	●	●	●	
38	19	25	SPXF 38	28.00–37.99	SP_F 38	6.00–25.00	●	●	●	●	●	●	
45	19	25	SPXF 45	35.00–44.99	SP_F 45	6.00–25.00	●	●	●	●	●	●	

Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.

TuffPunch Regular Center Dowel Blanks



Material
Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOWTOORDER

Specify:	Qty.	Type	D Code	L
Example:	6	SPBF	25	110

Standard Alterations
See p.12 for additional ordering instructions.


Shank D	Catalog Number	L					
		80	90	100	110	120	130
10	SPBF 10	●	●	●	●	●	●
13	SPBF 13	●	●	●	●	●	●
16	SPBF 16	●	●	●	●	●	●
20	SPBF 20	●	●	●	●	●	●
25	SPBF 25	●	●	●	●	●	●
32	SPBF 32	●	●	●	●	●	●
38	SPBF 38	●	●	●	●	●	●
45	SPBF 45	●	●	●	●	●	●

Note: DayKool™ (XCR)—a cryogenic steel conditioning process used primarily with hard, thick materials to improve strength, toughness, and dimensional stability—is standard on all Dayton TuffPunch® products. For additional information, see p. 2.

Trumpet Head Jektol® Punches

Conforms to DIN and ISO Standards


NEW



Type
AV_BJ


Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOW TO ORDER


Specify: Qty. Type D Code L P (or P&W) Dimension
Example: 6 AVXBJ 16 19-80 P 10.3
12 AVRBj 16 25-80 P 10.5, W 8.0
10 AVLBJ 16 19-90 P 10.2, W 7.2



- 1 Check your P&W dimensions to be certain the diagonal G does not exceed the maximum shown.
- 2 Centerline to flat minimum = 2.0 for J6 and 3.0 for J9.

Note: Sharp corners will have a 0.13 radius to minimize wear.

Note: The standard location of a key flat is parallel to the P dimension. For additional information, see p.13.




Standard Alterations
See p.12 for additional ordering instructions.

D	Type	D2	H	k	f	r	Min	Max	L1				L				Jektol
							W	P/G					71	80	90	100	
5	AV_BJ	7,0	4,0	1,5	15°	10,0	2,00	5,00	10	13	-	-	•	•	•	•	J2M
6	AV_BJ	9,0	4,0	1,5	20°	10,0	2,40	6,00	10	13	-	-	•	•	•	•	J3M
8	AV_BJ	11,0	4,0	1,5	30°	12,0	3,00	8,00	13	19	25	-	•	•	•	•	J4M
10	AV_BJ	14,0	4,0	1,5	35°	15,0	5,00	10,00	13	17	19	25	•	•	•	•	J6M
13	AV_BJ	17,0	4,0	1,5	40°	15,0	7,50	13,00	13	17	19	25	•	•	•	•	J6M
16	AV_BJ	20,0	4,0	1,5	40°	15,0	10,00	16,00	13	17	19	25	•	•	•	•	J9M
20	AV_BJ	25,0	4,0	1,5	40°	15,0	15,00	20,00	13	17	19	25	•	•	•	•	J9M

Trumpet Head Jektol Blank

Conforms to DIN and ISO Standards


NEW



Type
AWXBJ

Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOW TO ORDER

Specify: Qty. Type L P Code
Example: 6 AWXBJ 80 16

Standard Alterations
See p.12 for additional ordering instructions.


Jektol® side hole position allows alternate point lengths shown on AV_BJ above.

P	Type	D2	H	k	f	r	L				Jektol
							71	80	90	100	
5	AWXBJ	7,0	4,0	1,5	15°	10,0	•	•	•	•	J2M
6	AWXBJ	9,0	4,0	1,5	20°	10,0	•	•	•	•	J3M
8	AWXBJ	11,0	4,0	1,5	30°	12,0	•	•	•	•	J4M
10	AWXBJ	14,0	4,0	1,5	35°	15,0	•	•	•	•	J6M
13	AWXBJ	17,0	4,0	1,5	40°	15,0	•	•	•	•	J6M
16	AWXBJ	20,0	4,0	1,5	40°	15,0	•	•	•	•	J9M
20	AWXBJ	25,0	4,0	1,5	40°	15,0	•	•	•	•	J9M

Trumpet Head Regular Punches

Conforms to DIN and ISO Standards


NEW



Type
AV_B


Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55




HOW TO ORDER

Specify:	Qty.	Type	D Code	L	P (or P&W) Dimension
Example:	6	AVXB	16	19-80	P 10.3
	12	AVRB	16	25-80	P 10.5, W 8.0
	10	AVLB	16	19-70	P 10.2, W 7.2



Note: The standard location of a key flat is parallel to the P dimension.
For additional information, see p.13.



Standard Alterations
See p.12 for additional ordering instructions.

D	Type	D2	H	k	f	r	Min	Max	L1				L			
							W	P/G					71	80	90	100
5	AV_B	7,0	4,0	1,5	15°	10,0	2,00	5,00	10	13	-	-	•	•	•	•
6	AV_B	9,0	4,0	1,5	20°	10,0	2,40	6,00	10	13	-	-	•	•	•	•
8	AV_B	11,0	4,0	1,5	30°	12,0	3,00	8,00	13	19	25	-	•	•	•	•
10	AV_B	14,0	4,0	1,5	35°	15,0	5,00	10,00	13	17	19	25	•	•	•	•
13	AV_B	17,0	4,0	1,5	40°	15,0	7,50	13,00	13	17	19	25	•	•	•	•
16	AV_B	20,0	4,0	1,5	40°	15,0	10,00	16,00	13	17	19	25	•	•	•	•
20	AV_B	25,0	4,0	1,5	40°	15,0	15,00	20,00	13	17	19	25	•	•	•	•

Trumpet Head Regular Punch Blanks

Conforms to DIN and ISO Standards


NEW



Type
AWXB

Material

Steel: PS4 (CPM M4), RC 60-62
Heads RC 40-55



HOW TO ORDER


Specify:	Qty.	Type	L	P Code
Example:	6	AWXB	80	20

Standard Alterations
See p.12 for additional ordering instructions.

P	Type	D2	H	k	f	r	L			
							71	80	90	100
5	AWXB	7,0	4,0	1,5	15°	10,0	•	•	•	•
6	AWXB	9,0	4,0	1,5	20°	10,0	•	•	•	•
8	AWXB	11,0	4,0	1,5	30°	12,0	•	•	•	•
10	AWXB	14,0	4,0	1,5	35°	15,0	•	•	•	•
13	AWXB	17,0	4,0	1,5	40°	15,0	•	•	•	•
16	AWXB	20,0	4,0	1,5	40°	15,0	•	•	•	•
20	AWXB	25,0	4,0	1,5	40°	15,0	•	•	•	•

Mounting Ring for Trumpet Head Punches

NEW



ITEM	D1	R	D2	D3	L	L1
RRT05	05	10	8.8	7	7	11
RRT06	06	10	10.8	9	7	11
RRT08	08	12	12.8	11	7	11
RRT10	10	15	15.8	14	9	13
RRT13	13	15	19.8	17	9	13
RRT16	16	15	21.8	20	9	13
RRT20	20	15	27.8	25	9	13

Mounting Rings for Trumpet Head Punches are easy way to install securely into your punch retainer or holder.

Counterbore the retainer to the "L1" dimension to accommodate the Ring and Punch head.


Mounting rings are made from tempered steel

HOW TO ORDER

Specify: Qty. Type D Code
Example: 6 RRT 20

Radius Cutter for Trumpet Head Punches

NEW



ITEM	d1 _{h7}	d2 _{h8}	d3 _{h11}	R	L1	L2
CST05	05	7.4	8	10.0	5	9.7
CST06	06	9.5	8	10.0	5	10.6
CST08	08	11.5	8	12.0	5	11.2
CST10	10	14.5	10	15.0	8	15.9
CST13	13	17.5	10	15.0	8	15.9
CST16	16	20.5	10	15.0	8	15.8
CST20	20	25.5	16	15.0	8	16.7

Use this Radius Tool Cutter on your punch retainers and blocks to accommodate Trumpet Head tooling


Can be used in place of Mounting Rings shown above.

HOW TO ORDER

Specify: Qty. Type D Code
Example: 6 CST 20

TuffPunch® Single Head Retainers

(Not for Trumpet Head Style)




HOWTOORDER




Specify:	Qty.	Type	D
Example:	4	ARTF	10
	6	ARTFS	25

ARTF and ARTFS TuffPunch® Retainer sets include:

- 2 Screws
- 2 Dowels



Backing Plate	
D	Catalog No.
10	URBP 10 63
13	URBP 13 63
16	URBP 16 63
20	URBP 20 63
25	URBP 25 63



Catalog No.		D	A	B	ARTF	ARTFS	Screw
Type	Code	D	A	B	H	M	Size
ARTF ARTFS	10	10.00	44.5	43.7	15.5	7.75	M8
	13	13.00	50.8	50.0	18.5	9.25	M8
	16	16.00	54.0	53.2	21.5	10.75	M8
	20	20.00	60.3	59.5	25.5	12.75	M10
	25	25.00	69.9	69.1	30.5	15.25	M12

Features/Benefits

TuffPunch® ARTF and ARTFS Single Head Punch Retainers are designed specifically for use with TuffPunch® Punches—Jektol® and Regular. Only one dowel is required for round punches, reducing machining time by up to 50%. The in-line center dowel assures precise punch-to-matrix alignment, giving you higher quality parts, longer punch life, and reduced downtime. Shaped punches use a secondary dowel for precise alignment.

Use of the TuffPunch® Center Dowel Punch and Retainer also eliminates hand-fitting, cutting mounting time by nearly 50%. Simply pull the retainer from its box, and screw it into the die set. This TuffPunch® combination gives you true dimensional accuracy every time.

Standard Alterations—Punches and Punch Blanks

Standard Alterations

Punches are available in sizes other than those listed on the individual product pages.


Jektol[®], Regular, and Center Dowel

XP, XW

P & W Dimensions
Smaller than Standard

XBR

(Straight Before Radius)
It is recommended that point lengths be kept as short as possible for optimum strength.



XL

Overall Length Shortened (25 min.)
Stock removal from point end, which shortens L₁ length.

XLB

Overall Length Shortened
Stock removal from end point. Point length L₁ maintained. (Min. shank length 25)

LL

Precision Overall Length
Same as XL except overall length is held to ±0.02.

XK



No Side Hole
For air ejection. No cost.

XS

Shear Angles
See information at right.

XJ

Smaller Jektol Components



L ₁ Max.	●	8	13	19	25	30	35	40	Jektol [®] Group
D Code	Type	Min. P (Rounds)							
08	AJXF	3.0	3.0	3.0	4.0	5.0	---	---	J4M
	APXF	1.5	1.5	1.5	2.0	2.0	2.0	4.0	---
10	AJXF	4.0	4.0	4.0	4.0	5.0	5.0	---	J6M
	APXF	1.5	1.5	1.5	2.0	2.0	2.0	2.0	---
	SJXF	4.0	4.0	4.0	4.0	5.0	5.0	6.0	J6M
	SPXF	1.5	1.5	1.5	2.0	2.0	2.0	4.0	---
13	AJXF	4.0	4.0	4.0	4.0	5.0	5.0	---	J6M
	APXF	3.0	3.0	3.0	3.0	3.0	3.0	4.0	---
	SJXF	---	4.0	4.0	4.0	5.0	5.0	6.0	J6M
	SPXF	3.0	3.0	3.0	3.0	3.0	3.0	4.0	---
16	AJXF	6.0	6.0	6.0	6.0	6.0	6.0	---	J9M
	APXF	5.0	5.0	5.0	5.0	5.0	5.0	5.0	---
	SJXF	---	6.0	6.0	6.0	6.0	6.0	6.0	J9M
	SPXF	5.0	5.0	5.0	5.0	5.0	5.0	5.0	---
20	AJXF	6.0	6.0	6.0	6.0	6.0	6.0	---	J9M
	APXF	6.0	6.0	6.0	6.0	6.5	6.5	6.5	---
	SJXF	---	6.0	6.0	6.0	6.0	6.0	6.0	J9M
	SPXF	6.0	6.0	6.0	6.0	6.5	6.5	6.5	---
25	AJXF	8.0	8.0	8.0	8.0	8.0	8.0	---	J9M
	APXF	8.0	8.0	8.0	8.0	9.0	9.0	9.0	---
	SJXF	---	8.0	8.0	8.0	10.0	10.0	10.0	J9M
	SPXF	8.0	8.0	8.0	8.0	9.0	9.0	9.0	---
32	SJXF	---	10.0	10.0	10.0	10.0	10.0	10.0	J9M
	SPXF	8.0	8.0	8.0	8.0	9.0	9.0	9.0	---
38	SJXF	---	10.0	10.0	10.0	10.0	10.0	10.0	J9M
	SPXF	8.0	8.0	8.0	8.0	9.0	9.0	9.0	---
45	SJXF	---	10.0	10.0	10.0	10.0	10.0	10.0	J9M
	SPXF	8.0	8.0	8.0	8.0	9.0	9.0	9.0	---

L ₁ Max.	●	8	13	19	25	30	35	40	Jektol [®] Group
D Code	Type	Min. P (Shapes)							
08	AJ_F	3.0	3.0	3.0	4.0	4.0	---	---	J4M
	AP_F	1.0	1.5	3.0	3.0	4.0	5.0	---	---
10	AJ_F	4.0	4.0	4.0	4.0	4.0	5.0	---	J6M
	AP_F	1.25	1.5	3.0	3.0	4.0	5.0	---	---
	SJ_F	4.0	4.0	4.0	4.0	4.0	4.5	6.0	J6M
	SP_F	1.25	1.5	3.0	3.0	4.0	5.0	---	---
13	AJ_F	4.0	4.0	4.0	4.0	4.0	5.0	---	J6M
	AP_F	1.5	1.5	3.0	3.0	4.0	5.0	---	---
	SJ_F	---	4.0	4.0	4.0	4.0	4.5	6.0	J6M
	SP_F	1.5	1.5	3.0	3.0	4.0	5.0	---	---
16	AJ_F	6.0	6.0	6.0	6.0	6.0	6.0	---	J9M
	AP_F	2.0	2.0	3.0	3.5	5.0	6.0	---	---
	SJ_F	---	6.0	6.0	6.0	6.0	6.0	6.0	J9M
	SP_F	2.0	2.0	3.0	3.5	5.0	6.0	---	---
20	AJ_F	6.0	6.0	6.0	6.0	6.0	6.0	---	J9M
	AP_F	2.5	2.5	3.0	3.5	5.0	6.0	---	---
	SJ_F	---	6.0	6.0	6.0	6.0	6.0	6.0	J9M
	SP_F	2.5	2.5	3.0	3.5	5.0	6.0	---	---
25	AJ_F	6.0	6.0	6.0	6.0	6.0	6.0	---	J9M
	AP_F	3.0	3.0	3.0	3.5	5.0	6.0	---	---
	SJ_F	---	6.0	6.0	6.0	6.0	6.0	6.0	J9M
	SP_F	8.0	8.0	8.0	8.0	9.0	9.0	9.0	---
32	SJ_F	---	7.2	7.2	7.2	7.2	7.2	7.2	J9M
	SP_F	3.0	3.0	3.0	3.5	5.0	6.0	---	---
38	SJ_F	---	7.2	7.2	7.2	7.2	7.2	7.2	J9M
	SP_F	3.0	3.0	3.0	3.5	5.0	6.0	---	---
45	SJ_F	---	7.2	7.2	7.2	7.2	7.2	7.2	J9M
	SP_F	3.0	3.0	3.0	3.5	5.0	6.0	---	---

Note: For surface coatings information, see p. 2 and the individual product pages.

Shear Angles (XS)

TuffPunch[®] products are available in common shear angle configurations for all standard shapes. Shear angles are also available for classified shapes as special orders.


Shear angles are available in any angle. Specify angle in whole degrees. If half degree is necessary, specify as a decimal, e.g., 8.5°. (Tolerance on all angles is ±15 minutes.) Use the chart below to determine the product designation, then simply add the alteration code shown next to the drawings, along with the angle desired.

Example: APXF 16-90-80 P 8.3 XS20 A5°.


For Round Punches Only

Views are reflected view.

XS19
Nail Point




XS20
Chamfer




For Round and Shape Punches


XS21
Conical




XS22
Double Shear



XS23
Single Shear




XS24
Single Shear
Angle with Flat



Locking Devices—Flats vs. Dowel Slots

Orientation

The standard location for all locking devices is 0°, and is always on the long side (P) of the shape. Custom locations are measured counterclockwise from 0°.




Standard and Alternate Locations

Definitions: Standard Location is at 0°. Alternate Location is 90°, 180°, or 270°. Alternate locations are available at no additional charge.

Custom Locations

Definitions:
Custom Location is any angle other than: 0°, 90°, 180°, or 270°.

Single Flats




Single Flats: X2

Order Example: X2 — 90°

Single Flats: X5

Order Example: X5 — 135°

Double Flats




Double Flats: X3

Locking Devices: X3
Order Example: X3 — 90°
Second Flat is always parallel to the first flat.

Double Flats: X6

Locking Devices: X6
Order Example: X6 — 135°

Additional Flats




Additional Flats

Code	Depth	Length
X81	1.5	13
X82	1.5	16
X83	1.5	20
X84	1.5	Full Length
X85	2.5	13
X86	2.5	16
X87	2.5	20
X88	2.5	Full Length
X89	Specify Dimensions	

Additional Flats

Code	Depth	Length
X91	1.5	13
X92	1.5	16
X93	1.5	20
X94	1.5	Full Length
X95	2.5	13
X96	2.5	16
X97	2.5	20
X98	2.5	Full Length
X99	Specify Dimensions	

Dowel Slots



Dowel Slots: X4 & X41

For standard locations, specify X4 (3.0 Dowel) or X41 (4.0 Dowel). For alternate locations, specify X4 or X41 and degree required.

Order Example: X4 — 90°

Dowel Slots: X7 & X71

Specify X7 (3.0 Dowel) or X71 (4.0 Dowel). For custom locations, specify X7 or X71 and degree required.

Order Example: X71 — 135°

Location Tolerance

Flat		Dowel	
F	Radial	F	Radial
+ 0.013 - 0.0	.025/25.0 inch	+ 0.013 - 0.0	0°4'

How To Specify

The most common locking devices—flat, double flat, and dowel—are available. Simply select the type, then add the code to the component description.

HOWTOORDER

Specify: Qty. Type D Code L P (or P&W) Locking
Dimension Device
Example: 1 AJRF 16 25-80 P8.5, W.8.0 X2

Other Dayton Products

Ball Lock Punches, Matrixes, Pilots, & Retainers

Dayton Ball Lock Products are mainstays in industries with high-demand applications, including automotive and major appliance manufacturing. Because there is no need to pull a die from the press, removal and replacement of worn punches can reduce downtime and improve profitability.

Dayton True Position® Retainers (the recognized industry standard) eliminate hand fitting, reduce mounting time, and are ideally suited for both round and complex-shaped products. True Position® allows easy replacement of broken or worn punches.



MaxLife® Die Springs


Dayton MaxLife® Die Springs are: made to exact specifications; manufactured to outperform and outlast other major brands; designed specifically for press and mold dies; and ensure optimum operation in heavy industry applications. Corrosion-resistant Dayton die springs are made from pre-tempered chrome silicon wire, and optimize the working life of press and mold dies.



Urethane Stripping & Forming Products

Durable, yet flexible, Dayton urethane strippers and forming products provide superior stripping over conventional strippers; develop higher load-bearing capacity; are tear- and oil-resistant; provide exceptional dampening; and are easy to install and replace.

Dayton dual durometer SMARTStrip™ Strippers (two elastomers molded into a single piece) are a cost-effective alternative to metal spring strippers.



Dayton provides a full range of leading-edge die component products: headed punches, guides, and matrixes; positive-locking Ball Lock products; retainers; slug-ejection punches; retaining systems; die springs; and others. For details, contact Dayton Lamina or your nearest Dayton Lamina Distributor.

* True Position and MaxLife are registered trademarks of Dayton Lamina.
™ SMARTStrip is a trademark of Dayton Lamina.



EVERYTHING YOU NEED. ALL IN ONE PLACE

Our enhanced website gives you the tools, information, and support you need to work smarter and perform better.



LIVE CHAT WITH A REAL PERSON

Connect instantly with our Customer Service team for answers when you need them.



ONCE YOU HAVE YOUR FREE ACCOUNT, YOU CAN:



GET INSTANT QUOTES

On thousands of standard items.



DOWNLOAD PART FILES

2D drawings and 3D models.



CONFIGURE PUNCHES & BUTTONS

Build custom tools and create downloadable models.



REVIEW ORDER HISTORY

View past orders, quotes, and invoices.



ORDER ONLINE


Quick, easy ordering—anytime, anywhere.

TECHNICAL RESOURCES THAT WORK FOR YOU



Explore a full library of technical articles, best practices, and application tips to help you improve performance and extend tool life.

- ✓ Material guides
- ✓ Tooling tips
- ✓ Troubleshooting advice
- ✓ Design best practices
- ✓ And much more!



POWERFUL TOOLS AT YOUR FINGERTIPS



Use built-in calculators and engineering tools to get accurate results fast.

- ✓ Die Calculator
- ✓ Die Clearance Calculator



EXPERIENCE THE NEW DAYTONLAMINA.COM
Smarter tools. Expert support. Built for your success.

GET STARTED TODAY!
Create your free account at
www.daytonlamina.com



Commitment to Quality & Customer Satisfaction

Dayton Lamina is a leading manufacturer of tool, die and mold components for the metal-working and plastics industries. As a customer-focused, world-class supplier of choice, we provide the brands, product breadth, distribution network and technical support for all your metal forming needs.

Our goal is to give our customers the most innovative and value added products and services



*Dayton Lamina's line of Danly products is available only to North America.

www.daytonlamina.com